



Turnbuckles Eye - Eye commercial pattern

- **Material** : drop forged mild steel
- **Standard** : DIN 1480
- **Finish** : electro-galvanised

diameter thread	length closed position	length open position	length body	length endfitting	length thread	diameter eye outside	diameter eye inside	weight each
a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
6	160	246	110	80	55	20	9	0.11
8	168	248	110	84	57	22	10	0.20
10	210	300	125	105	68	31	14	0.28
12	222	305	125	110	70	35	16	0.43
14	244	334	140	123	75	40	18	0.61
16	300	416	170	143	88	47	22	1.00
20	334	466	200	165	105	52	24	1.60
22	372	527	220	185	118	60	27	2.20
24	410	587	255	208	135	65	27	2.80
30	440	605	255	220	135	71	31	4.10
33	490	690	295	245	148	88	36	6.00
36	554	740	295	277	158	94	38	8.50



Turnbuckles Hook - Hook commercial pattern

- **Material** : drop forged mild steel
- **Standard** : DIN 1480
- **Finish** : electro-galvanised

diameter thread	length closed position	length open position	length body	length endfitting	length thread	opening hook	thickness hook	weight each
a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
6	184	270	110	92	55	8	15	0.11
8	200	280	110	100	57	10.5	15	0.20
10	234	323	125	117	68	13	11	0.28
12	260	343	125	130	70	16	13	0.43
14	278	368	140	139	75	18	15	0.61
16	322	438	170	161	88	20	17	1.00
20	382	514	200	191	105	21	21	1.60
22	456	601	220	228	118	24	28	2.20
24	496	673	255	248	135	26	33	2.80
30	550	715	255	275	135	34	35	4.10
33	600	799	295	300	148	38	40	6.00
36	640	825	295	320	158	46	45	8.30