



Yoke Snatch Block with Captive Shackle


Meets or exceeds the requirements specified in ASME B30.26 - 2010.

Yoke Snatch Blocks are manufactured from the highest quality tensile steel.

Snatch Blocks are supplied with bronze bushings and grease fitting for ease of use and extended shelf life.


Designed with a safety factor 4 : 1.

Available in sizes 2 tonnes to 20 tonnes.



DIMENSIONAL SPECIFICATIONS

Part Code	WLL tonnes	Sheave Dia. mm	Wire Rope Size mm	a mm	b mm	e mm	f mm	g mm	k mm	l mm	r mm	Mass kg
8-501-02	2.0	76	8-10	35	30	64	11	75	150	228	217	3.8
8-501-04	4.0	114	10-13	64	50	79	19	107	243	356	336	6.2
8-501-08	8.0	152	16-19	87	76	104	32	152	320	484	452	13.2
8-501-0808	8.0	203	16-19	87	76	104	32	220	333	558	526	18.2
8-541-12	12.0	152	19-22	78	80	134	44	167	359	540	496	24.8
8-541-15	15.0	203	19-22	78	80	134	44	220	355	589	545	29.6
8-541-1510	15.0	254	19-22	78	80	134	44	280	423	714	670	42.7
8-501-1512	15.0	305	19-22	78	80	134	44	330	428	770	726	52.8
8-551-20	20.0	203	25-29	109	93	150	55	216	433	671	616	41.6
8-551-2010	20.0	254	25-29	109	93	150	55	280	481	778	723	52.4
8-551-2012-29	20.0	305	25-29	109	93	150	55	330	485	883	778	62.8




Part Code	WLL tonnes	Sheave Dia. inches	Wire Rope Size inch	a inch	b inch	e inch	f inch	g inch	k inch	l inch	r inch	Mass lbs.
8-501-02	2	3	5/16 - 3/8	1.38	1.18	2.52	0.43	2.95	5.91	8.96	8.53	4.4
8-501-04	4	4-1/2	3/8 - 1/2	2.52	1.97	3.11	0.75	4.21	9.57	14.02	13.27	13.0
8-501-08	8	6	5/8 - 3/4	3.43	2.99	4.09	1.26	5.98	12.60	19.06	17.80	28.7
8-501-0808	8	8	5/8 - 3/4	3.43	2.99	4.09	1.26	8.66	13.10	21.90	20.64	43.0
8-541-12	12	6	3/4 - 7/8	3.07	3.15	5.28	1.73	6.57	14.13	21.26	19.63	53.6
8-541-15	15	8	3/4 - 7/8	3.07	3.15	5.28	1.73	8.66	13.99	23.19	21.46	65.1
8-541-1510	15	10	3/4 - 7/8	3.07	3.15	5.28	1.73	11.00	16.70	28.10	26.37	94.8
8-501-1512	15	12	3/4 - 7/8	3.07	3.15	5.28	1.73	13.00	16.80	30.30	28.57	117.9
8-551-20	20	8	1 - 1-1/8	4.29	3.66	5.91	2.17	8.50	17.05	26.42	24.25	90.8
8-551-2010	20	10	1 - 1-1/8	4.29	3.66	5.91	2.17	11.00	18.90	30.60	28.46	119.0
8-551-2012-29	20	12	1 - 1-1/8	4.29	3.66	5.91	2.17	13.00	19.10	32.80	30.63	137.8

Loads On Blocks

Angle Factor Multipliers

The Working Load Limit (WLL) for Yoke Group blocks indicates the maximum load that should be exerted on the block and its connecting fitting. This total load value may be different from the weight being lifted or pulled by a hoisting system. It is necessary to determine the total load being imposed on each block in the system to properly determine the rated capacity block to be used. A single sheave block used to change load line direction can be subjected to total loads greatly different from the weight being lifted or pulled. The total load value varies with the angle between the incoming and departing lines to the block. The following chart indicates the factor to be multiplied by the line pull to obtain the total load on the block.



Angle	Factor	Angle	Factor
0	2.00	100	1.29
10	1.99	110	1.15
20	1.97	120	1.00
30	1.93	130	0.84
40	1.87	135	0.76
45	1.84	140	0.68
50	1.81	150	0.52
50	1.73	160	0.35
70	1.64	170	0.17
80	1.53	180	0.00
90	1.41	-	-

Contact Us

Tel: 0117 9381 600
 Fax: 0117 9381 602
 email: sales@safetyliftinggear.com

Unit R1D Rockingham Gate
 Poplar Way West
 Cabot Park
 Bristol
 BS11 0YW



Sheave Size And Wire Rope Strength

Ratio A	Strength Efficiency Compared to Catalogue Strength in %	Ratio A	Strength Efficiency Compared to Catalogue Strength in %
40	95	8	83
30	93	6	79
20	91	4	75
15	89	2	65
10	86	1	50

Ratio A = Sheave Diameter + Rope Diameter

Strength Efficiency

Bending wire rope reduces its strength. To account for the effect of bend radius on wire rope strength when selecting a sheave, use the table above.

Ratio B	Relative Fatigue Bending Life	Ratio B	Relative Fatigue Bending Life
30	10.0	16	2.1
25	6.6	14	1.5
20	3.8	12	1.1
18	2.9	-	-