Tubesca Probat Platform Step Ladder



Specifications

- Warranty: 5-year
- Max Load: 150kg
- Standard: EN131 Professional
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: FR
- Recommended Usage: Intensive

Common Dimensions

- Tread Depth: 100mm
- Distance Between Treads: 250mm
- Storage Depth: 310mm
- Top Platform Tread (LxW): 390 x 382mm
- Handrail Height: 700mm

Availability & Delivery

Stock item. Delivery next day. (See exceptions, if applicable, overleaf)

[Representative image of product]

Features

- Manufactured from 50mm aluminium scaffold tube for maximum rigidity and stability
- Mammoth 100mm deep steps for maximum climbing support
- Extra-strong 390 x 382mm bi-folding platform
- Large integrated metal tool tray with bucket hook
- Featuring tough spun-rung Duraclimb technology for intensive use
- Convex oversized feet ensure maximum ground contact and grip
- Ideal for use on construction sites and facilities maintenance

Product Dimensions

SKU	Treads ²	Approx. Working Height ¹ (mm)	Platform Height (mm)	Closed Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1205-004	4	2550	950	1910	690	980	10.8
1205-005	5	2800	1200	2160	720	1140	12.4
1205-006	6	3020	1420	2410	750	1300	14.5
1205-007	7	3260	1660	2660	780	1460	15.5
1205-008	8	3500	1900	2910	810	1620	17.0
1205-009	9	3730	2130	3160	840	1780	19.6
1205-010	10	3970	2370	3410	870	1940	21.5
1205-012	12	4440	2840	3910	930	2260	27.5

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

² Treads includes top platform step/top cap tool tray tread

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.



Tubesca Probat Platform Step Ladder

Product Description

The Probat Platform Step Ladder provides maximum stability and is designed for intensive use in the most demanding environments. It is over-tested to 360kg and with the front and rear stiles constructed using large 50mm aluminium scaffold tube. The mammoth 100mm deep treads are secured using Duraclimb spun-rung technology to provide the strongest possible mechanical connection for intensive use.

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1205-004	3178740025380	1910	690	310	0.409	12.1
1205-005	3178740025397	2160	720	310	0.482	14.0
1205-006	3178740025403	2410	750	310	0.56	16.4
1205-007	3178740025410	2660	780	310	0.643	17.7
1205-008	3178740025427	2910	810	310	0.731	19.6
1205-009	3178740025434	3160	840	310	0.823	22.5
1205-010	3178740025441	3410	870	310	0.92	24.7
1205-012	3178740025458	3910	930	310	1.127	31.3

Packaging Material: Polywrap & Wooden Battons

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.