

PHOENIX rescue harness QC

H11Q

Designed for fire and industrial rescue teams working in confined space, vertical rescue and fall arrest. Suitable for use with back-mounted breathing apparatus.

Features:

- Quick fit buckles for speed of fit
- Highly durable and comfortable to wear
- Integral back panel
- Semi-circular screwlink front attachment point
- High rear attachment point
- Protected leg loops
- Adjustable locking side buckles
- Captive buckles with large tabs

Integral back panel helps to maintain the structure of the harness.

Semi-circular screwlink permits safe multi-directional loading for casualty attachment.

Front attachment point is rated for fall arrest, it can be used for lowering or raising and suspension. Connector remains in position even if harness adjusted to fit.

Rear attachment point is rated for fall arrest and suspension, it is positioned high to be compatible with breathing apparatus and is reachable by the user.

Double thickness webbing provides added protection and wear resistance for the leg loops.

Adjustable side buckles allow for added comfort and sizing, but lock to prevent accidental release.

Leg loops have quick connect buckles for fast donning.

Buckles are captive to prevent disassembly.

Parking point allows attachment of lanyard, torch, radio etc



Specifications:

NB: specifications and colour may change without notice.

Size: Universal
EN Test Mass: 150kg
Loading: Fall Arrest & Rescue loads

Conformity: EN361, EN1497

Materials: Polyamide, Stainless Steel and Plated screwlink.

Weight (kg): 1.30

Industries: Fire and rescue service. Can be used as part of both fall arrest and suspension systems.

Attachment Points:

Dorsal
Sternal

Harness Measurements (cm):

Torso	95-130
Waist	-
Thigh	65-110