



- Chrome plated cylinder & ram
- Capacity: 10 to 150 tonne
- Equipped with a spring return
- Maximum pressure 700 bar
- Supplied with 3/8" NP7 female coupling
- Can be used in any position
- 200-1000 tonne can be made to order
- Supplied Fully tested & certified

Model	Tonnage (T)	Stroke (mm)	Oil Capacity (cm ³)	Matching Pump	Closed Height A (mm)	Extended Height B (mm)	Outside Diameter D (mm)	Inside Diameter E (mm)	Piston Diameter F (mm)	G.W. (kg)	
HHYG-1050	10	50	85	HHB-700	100	150	68	45	36	3.1	
HHYG-10100		100	169		172	272				4.4	
HHYG-10150		150	254		222	372				5.7	
HHYG-2050	20	50	157		108	158	83	60	45	4	
HHYG-20100		100	311		176	276				5.3	
HHYG-20150		150	465		226	376				6.6	
HHYG-3050	30	50	237		HHB-700-2000CC	114	164	103	75	65	7.9
HHYG-30100		100	471			187	287				10.7
HHYG-30150		150	705			237	387				13.5
HHYG-5050	50	50	389	120		170	123	95	70	11.6	
HHYG-50100		100	768	197		297				14.9	
HHYG-50150		150	1147	247		397				18	
HHYG-10050	100	50	833	HHB-700-3000CC	142	192	168	135	90	25.7	
HHYG-100100		100	1584		232	332				30.6	
HHYG-100150		150	2335		282	432				35.5	
HHYG-15050	150	50	1133		182	232	205	165	115	43	
HHYG-150100		100	2237		232	332				53	
HHYG-150150		150	3342		282	432				63	
				HHB-630A							