



N/A

In addition to routine che inspection every 12 months a PPE inspection should b Download the instructions at	and after any exceptional e conducted with the n		:t.	ection by a compete	nt person. Petzl recc	ommends a	 រn		
ASAP'SOF	RBER							_	
User information				PPE information					
Surname				Model					
Address				Serial number					
				Year of manufacture					
				Date of purchase					
Identifier				Date of first use					
				Manufacturer: Petz	zl, Zl Cidex 105A - 38	920 Crolle	s - Franc	æ	
\oslash		Q	X						N/A
Good condition (G)	To mo	onitor (TM)	To repair (T	R)	Do not use, retire (F	R)		Not a	applicable
2. Preliminary observations						\oslash	Q	X	
Verify the presence and legit Verify that the product lifetim Compare with a new device	pility of the serial number a le has not been exceeded	l.	S.						
3. PreparationDepending on your model, r	emove the CAPTIVs, cara	abiners and STRING, or remo	ve the ASAP'SOF	RBER from the ASAP	LOCK.				
4. Checking the condition of • Check the condition of the p Open the pouch and pull ou • Check the condition of the s • Verify that the energy absort • On the ASAP'SORBER inter • Check the condition of the c • Put the energy absorber bac • Verify that all of the energy a	ouch. Look for wear and t the energy absorber. nergy absorber. Look for afety stitching on both sic per has not sustained an ii national version and ASA connection points. Look for k in the pouch and close	damage due to use (cuts, fuz wear and damage due to use les. Look for any threads that mpact load (verify that none of P'SORBER AXESS, verify tha or wear and damage due to u it.	e (cuts, fuzziness, t are loose, worn, of the fabric betw at the fall indicator	signs of chemicals) or cut. een the straps has bee has not been torn.	en torn).				
 5. Checking the condition of • For connector inspection, see 		your connector model at Pet	zl.com.						
6. Checking the protection • Check the condition of the S • Reinstall the STRINGs on th • Verify that the STRING corre • Verify that the STRING corre • Reinstall the connectors. If a	TRINGs. e attachment points. g/STRING assembly is co ctly positions the connect	tor.							

VERDICT			Inspected by				
	Product fit to remain in service		Company				
Product unfit to remain in service			Date	Next inspection date			

PPE INSPECTION - Inspection form - ASAP'SORBER (151018)

Comments (detail here any defects found on the product and accomplished tasks)