

- In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 - PPE inspection should be conducted with the manufacturer's Instructions for Use.
- Download the instructions at [PETZL.COM](https://www.petzl.com).

PULLEYS

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France



Good condition (G)



To monitor (TM)



To repair (TR)



Do not use, retire (R)

N/A

Not applicable

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):



N/A

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new product to verify there are no modifications or missing parts.

3. Checking the condition of the side plates

- Check the condition of the side plates (marks, deformation, cracks, wear, corrosion).
- Check the condition of the attachment holes (marks, deformation, cracks, wear, corrosion...).
- For pulleys with moving side plates, verify that the side plates rotate properly.
- Check the condition of the rivets (marks, deformation, cracks, corrosion, absence of play...).
- Check the condition (marks, deformation, cracks, wear, corrosion) and the rotation of the swivel in both directions.

4. Checking the condition of the sheave(s)

- Check the condition of the sheave (marks, deformation, cracks, wear, corrosion, absence of foreign bodies...).
- Verify that the sheave turns freely in both directions.

Sheave on ratcheting wheel, SPIN L1D

- Check the condition of the ratcheting wheel (marks, deformation, cracks, wear, corrosion...). Verify that the sheave turns in the desired direction and blocks in the other direction.
- Count the number of clicks of the ratcheting wheel. You must hear 12 clicks during one complete rotation.

5. Checking the side plates' opening and locking systems

- Check the condition and function of the locking system (marks, deformation, dirt, effectiveness of the return spring(s)).

6. Function check

- Install your pulley on an anchor and install a compatible rope around the sheave.
- Circulate the rope in both directions.

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date

Next inspection date