

• **In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person.** Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.  
 • **PPE inspection should be conducted with the manufacturer's Instructions for Use.**  
 Download the instructions at [PETZL.COM](http://PETZL.COM).

## JAG SYSTEM

### User information

Surname

Address

Identifier

### PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

**Manufacturer:** Petzl, ZI Cidex 105A - 38920 Crolles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

### 1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

				N/A
---	---	---	---	-----

### 2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

### 3. Removing the connectors and the cover

- Remove the connectors and inspect them using the corresponding inspection procedure.0
- Collapse the cover.
- Inspect JAG and JAG TRAXION using the corresponding inspection procedures.

### 4. Inspecting the rope

- Check the condition of the sewn loop on the JAG TRAXION.  
Move this loop to inspect the hidden parts of the JAG TRAXION attachment hole.
- Check the condition of the sheath over the full length of the rope (cuts, wear, burns, fuzzy areas or signs of chemical products...).
- Do a tactile inspection of the core along the full length of the rope (hard spots, swelling, soft or crushed areas...).
- Check the stitching. Make sure there are no cut, torn, loose, or worn threads.

### 5. Inspecting the cover

- If necessary, remove the cover and replace it with a JAG SYSTEM replacement cover.

### 6. Installing the connectors

- Check that the rope is not tangled before reassembling the system.
- Reinstall the connectors.
- Verify that the connectors are correctly positioned in the JAG and JAG TRAXION attachment holes.

### 7. Function check

- Install your JAG SYSTEM on an anchor at low height, with a light load.
- Verify that the system locks under load.
  - Verify that the JAG TRAXION can be deactivated for a short descent.
  - Verify that the load can be hauled.

### Comments (detail here any defects found on the product and accomplished tasks)

### VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date

Next inspection date